

B	20.10.2009	21	8706	22	40300000	-	L	03	9	-	P2 P4	/-	t	-
J	54	4	0200				18	08870--		19	2550--			
E	WSK00000001236372			3	4		20	3250--		6	06400--			
D1	SCHMITZ GOTHA						12	-	13	12000	Q	-		
	SKI 24						V.7	-	F.1	039000	F.2	035000		
	A						7.1	09000	7.2	09000	7.3	09000		
D.2	FE1B9B						8.1	08000	8.2	08000	8.3	08000		
							U.1	-	U.2	-	U.3	-		
D.3	SKI 24 SL06-7.2						0.1	-	0.2	-	S.1	-	S.2	-
2	SCHMITZ GOTHA						15.1	385/65R22.5 160J						
5	SAFH KIPPER OFF.KASTEN						15.2	385/65R22.5 160J						
							15.3	385/65R22.5 160J						
V.9							R	-		11				
14							K	L582*01						
P.3							6	29.05.2006	17	K	16	VB172334		
10							21	GRÜNES KENNZEICHEN						
22	VOR BEGINN DER FAHRT PLANENHALTER NACH INNEN UMSTECKEN													
	UND H+S VENTIL IN FAHRTSTELLUNG BRINGEN*FZ DARF NUR H													
	INTER ZUGFZ.MIT STECKVERBINDUNG NACH ISO 7638 (5 ODER													
	7 POLIG)BETRIEBEN WERDEN**													