

27.07.2021	2.1	7686	2.2	ADU00073 9	L	2	9	-	P.2 P.4	-/-	T	-
Q2	4	DC02			18	3435-4225			19	1760-1845		
WWC2T1320MWN00056			3	5	20	545-3260			G	295-705		
WM MEYER					12		13	100		Q	-	
WM EG-BT25					V.2	-	F.1	2000		F.2	2000	
AA					7.1	1000	7.2	1000		7.3	-	
DAAAA					8.1	1000	8.2	1000		8.3	-	
					U.1	-	U.2	-		U.3	-	
WM EG-BT25,WM BT25,BT25					Q.1	-	Q.2	-		S1	-	S2 -
WM MEYER					151	165/80R13 B1J						
Anhänger > 0,75 - 3,5 t					152	165/80R13 81J						
DC offener Kasten					153	-						
-					R					11		
-					K	e1*2007/46*0809*02						
-					6	27.10.2014			17/	K	16	GC144612
-	141	-	P1	-	21							

B.AUSR.M.STOSSDÄMPFER U.REIFEN M.LAST-/GESCHW.-INDEX MIN.84
 ;GEM.4.ÄND.VO Z.9.AUSN.VO Z.STVO TEMPO 100KM/H I.KOMBINAT.
 /ENN ZUG-FZ M.ABV U.LEERMAS.MIN.1818KG ODER WENN ZUG-FZ ZUS
 M.SPEZ.FAHRDYN.STABI-SYST.F.ANH-BETR.LEERMAS.MIN.1667KG*