

10.06.13	2.1	3333	2.2	AXK038664	L	2	9	01	P.2 P.4	92	/3500	T	143
N1		4	BB		18	5548					19	2070	
VF1MAF4DC48933231				3	0	20	2482-2499					G	2002-2275
RENAULT						12	-	13	100	Q	-		
MA						V.7	209	F.1	3500	F.2	3500		
MAF4D						7.1	1850	7.2	2100	7.3	-		
MAF4DC						8.1	1850	8.2	2100	8.3	-		
-						0.1	82	0.2	2625	0.3	73		
MASTER						0.1	2500	0.2	750	S.1	3	S.2	-
RENAULT (F)						15.1	225/65 R 16 C(112/110)R						
Fz.z.Gü.bef. b. 3,5 t						15.2	225/65 R 16 C(112/110)R						
Van						15.3	-						
715/2007*630/2012I/EG						R						11	-/-
EURO5;I;PI/CI; N1 III, N2						K	e2*2007/46*0016*19						
Diesel						G	28.11.12	27	A	16	EE226644		
0002	141	3510	P1	2299	21								
ww.AHK lt. EGIG/ABE*Stufe PMK 4 ab Tag Erstzul.*Zu 0.1													
:max.3500kg bis 8%Steig.,dabei Zuggesamtgew.max.6800kg													
;D-Wert d.AHK min 17,17kN,zul.Stützlast 140kg,o.techn.													
Änd.*m.Anhängerkupplung -KMH, Herst.:Inovation Solution													
s,PZ:E1101-8382,ohne Auflagen oder Beschränk.*													